

APC EASY UPS BV 1000VA, AVR, Schuko Outlet, 230V

BV1000I-GR

Call for More Information 00234 0 807 819 1509 / 00234 0 709 850 4365



- Includes: User manual

Output	
Output power capacity	600 Watts / 1.0kVA
Max Configurable Power (Watts)	600 Watts / 1.0kVA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz Unsynchronised
Topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Output Connections	(4) Schuko CEE 7
Transfer Time	6 ms typical : 10 ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 5 Hz Auto-sensing
Input Connections	Schuko CEE 7/7P
Cord Length	1.5meters
Input voltage range for main operations	170 - 280V
Number of Power Cords	1

Batteries & Runtime	
Battery type	Lead-acid battery
Typical recharge time	8hour(s)
Nominal Battery Voltage	12 V
Expected Battery Life (years)	3 - 5

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC EASY UPS BV 1000VA, AVR, Schuko Outlet, 230V | BV1000I-GR | Downloaded on 10/13/2021 (EST)

Batteries & Runtime

Efficiency View Efficiency Graph (Available in Technical Tab on site)

Communications & Management

Control panel LED Status display with on line : on battery

Audible Alarm Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating 156Joules

Physical

Maximum Height 93MM, 9.25CM

Maximum Width 161MM, 16.05CM

Maximum Depth 305MM, 30.5CM

Net Weight 5.7KG

Shipping weight 6.0KG

Shipping Height 237MM, 23.7CM

Shipping Width 143MM, 14.3CM

Shipping Depth 373MM, 37.3CM

Color Black

SCC Codes 10731304338243

Environmental

Operating Temperature 0 - 40 °C

Operating Relative Humidity 0 - 90 %

Operating Elevation 0 - 2032.1meters

Storage Temperature -20 - 50 °C

Storage Relative Humidity 0 - 90 %

Storage Elevation 0 - 15240meters

Audible noise at 1 meter from surface of unit 40.0dBA

Protection Class IP20

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Conformance

Approvals CE, EN/IEC 62040-1, EN/IEC 62040-2

Standard warranty 2 years repair or replace

Sustainable Offer Status

RoHS Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.